



SKU : 101669

The drilling machines of the SSB F Super series are the right choice for every workshop, from maintenance to production. The sturdy drilling machines are constructed with a thick-walled column and powerful drives. The spindle speed is infinitely variable and the quill feed has a robust gearbox. Whether via the control panel or touchscreen, all functions are clearly displayed and are easy to use. The clamping table can be moved in height using a motor and facilitates the handling of heavy parts.

- High drilling and thread cutting capacity
- Infinitely variable speed
- Motorized table height adjustment
- Swiveling and rotating setup table
- Fully equipped

TECHNICAL SPECS

WORKING AREA

Drilling capacity	50 mm
Tapping capacity, steel	M 30
Table set up area	580 mm x 460 mm
Quill stroke	200 mm
Manual table travel	530 mm
Powered table travel	410 mm
Table swivel range (max.)	± 45°
Column diameter	180 mm
Spindle nose-to-table surface distance	590 mm
Spindle nose-to-foot distance	1175 mm
Throat depth	360 mm

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	1.15 m x 0.68 m x 2.36 m
Weight	650 kg

HEADSTOCK

Speed range	50 1/min - 2200 1/min
Spindle mount	4 MT

FEED

Quill feeds	0,08; 0,12; 0,17; 0,24; 0,35; 0,50 (6) mm/R
-------------	--

DRIVE CAPACITY

Motor rating main drive	2.2 kW
-------------------------	--------

PRODUCT DETAILS

Ideal for drilling, countersinking, reaming and tapping

- Very rigid construction with thick-walled column and large throat
- Infinitely variable speed adjustment and digital speed display
- 4 automatic drill feeds with electromagnetic clutch control and automatic shut-off when reaching the limit stop
- Motorized table height adjustments
- Digital boring depth display
- Large drilling table with circumferential coolant groove, height adjustment, and $\pm 45^\circ$ swivel range
- Tapping unit is Standard equipment

STANDARD EQUIPMENT

Thread cutting function
Protective shield
LED work lamp
Coolant system
Operating tools
Operator manual



Drill press table with motorized travel and adjustable angle

