



## PRODUCT.BROCHURE.SKU: 101669

The drilling machines of the SSB F Super series are the right choice for every workshop, from maintenance to production. The sturdy drilling machines are constructed with a thick-walled column and powerful drives. The spindle speed is infinitely variable and the quill feed has a robust gearbox. Whether via the control panel or touchscreen, all functions are clearly displayed and are easy to use. The clamping table can be moved in height using a motor and facilitates the handling of heavy parts.

- High drilling and thread cutting capacity
- Infinitely variable speed
- Motorized table height adjustment
- Swiveling and rotating setup table
- Fully equipped

## PRODUCT.BROCHURE.technical\_specs

### ATTRIBUTES.MEG-000008.DESCRPTION

|                                  |                 |
|----------------------------------|-----------------|
| attributes.MEG-000008.MER-000879 | 50 mm           |
| attributes.MEG-000008.MER-000111 | M 30            |
| attributes.MEG-000008.MER-000271 | 580 mm x 460 mm |
| attributes.MEG-000008.MER-000180 | 200 mm          |
| attributes.MEG-000008.MER-000744 | 530 mm          |
| attributes.MEG-000008.MER-000531 | 410 mm          |
| attributes.MEG-000008.MER-000577 | ± 45°           |
| attributes.MEG-000008.MER-000204 | 180 mm          |
| attributes.MEG-000008.MER-000258 | 590 mm          |
| attributes.MEG-000008.MER-000257 | 1175 mm         |
| attributes.MEG-000008.MER-001010 | 360 mm          |

### 000007.DESCRPTION

|                                  |                       |
|----------------------------------|-----------------------|
| attributes.MEG-000007.MER-000075 | 50 1/min - 2200 1/min |
| attributes.MEG-000007.MER-001749 | 4 MT                  |

### ATTRIBUTES.MEG-000006.DESCRPTION

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| attributes.MEG-000006.MER-000463 | 0,08; 0,12; 0,17; 0,24; 0,35; 0,50 (6) mm/R |
|----------------------------------|---------------------------------------------|

### ATTRIBUTES.MEG-000002.DESCRPTION

|                                  |        |
|----------------------------------|--------|
| attributes.MEG-000002.MER-000159 | 2.2 kW |
|----------------------------------|--------|

### ATTRIBUTES.MEG-000004.DESCRPTION

|                                         |                          |
|-----------------------------------------|--------------------------|
| attributes.MEG-000004.MER-000002-height | 1.15 m x 0.68 m x 2.36 m |
| attributes.MEG-000004.MER-000108        | 650 kg                   |

### ATTRIBUTES.MEG-

## PRODUCT.BROCHURE.PRODUCT\_DETAILS

### Ideal for drilling, countersinking, reaming and tapping

- Very rigid construction with thick-walled column and large throat
- Infinitely variable speed adjustment and digital speed display
- 4 automatic drill feeds with electromagnetic clutch control and automatic shut-off when reaching the limit stop
- Motorized table height adjustments
- Digital boring depth display
- Large drilling table with circumferential coolant groove, height adjustment, and  $\pm 45^\circ$  swivel range
- Tapping unit is Standard equipment

## PRODUCT.BROCHURE.STANDARD\_EQUIPMENT

