

Column Drilling Machines SSB F 60 Super VT PRO





TECHNICAL SPECS

WORKING AREA

| Drilling capacity | 2.36 in |
|---|---------------|
| Tapping capacity, steel | M 42 |
| Table set up area | 24 in x 20 in |
| Quill stroke | 8 in |
| Table swivel range (max.) | ± 45° |
| Table stroke | 21 in |
| Column diameter | 8 in |
| Throat | 15 in |
| Spindle nose-to-foot distance | 44 in |
| Spindle nose-to-table surface distance | 20 in |
| | |

HEADSTOCK

| Speed range | 50 - 316 316 - 2000 rpm |
|---------------|-------------------------|
| Spindle mount | 5 MT |

FEED

| Quill feeds | stufenlos "/rev | |
|-------------|-----------------|--|
| Quinticeus | Statemos /iev | |

DRIVE CAPACITY

| Motor rating main drive | 5.4 Hp |
|--|--------|
| Motor rating for vertical table travel | 0.5 Hp |
| Motor rating coolant pump | 0.2 Hp |

The drilling machines of the SSB F 60 Super VT series are the servo-

SKU:101680

Super VT series are the servoconventional solution for every workshop. This machine offers an electronically controlled servo quill feed with a large touchscreen operating display, which also supports the user in selecting the correct machining parameters. Feed and speed are infinitely variable. The entire design of the machine is very solid and the drilling performance is superior. This drilling machine is ideal for single and small series production, especially in the maintenance of large systems and in steel construction and workshops.

- High drilling and thread cutting capacity
- Servo motor for quill feed
- Touchscreen control panel with additional features
- Infinitely variable speed
- Motorized table height adjustments
- Swiveling and rotating setup table

MEASURES AND WEIGHTS

| Overall dimensions (length x width x height) | 41 in x 24 in x 90 in |
|---|-----------------------|
| Weight | 2090 lbs |











PRODUCT DETAILS

Ideal for drilling, countersinking, reaming and tapping

- Heavy construction with thick-walled column
- Base, column, table and gear head are made of premium high-quality cast iron •
- •
- •
- •
- Large drill press table with circumferential coolant groove and $\pm 45^{\circ}$ swivel range Table height adjustment via a powerful motorized drive Auxiliary gears of main spindle drive run in an oil-bath Easy handling of the machine ensures effortless operation in a production environment •
- Thread-cutting feature is standard •

STANDARD EQUIPMENT

Touchscreen controller Automatic thread cutting cycles Automatic drilling feed Motorized table height adjustment Drilling accessories Coolant system Protective shield LED work lamp Operator instructions