

Column Drilling Machines

SSB F 60 Super VT PRO





TECHNICAL SPECS

WORKING AREA

| 60 mm |
|-----------------|
| 00 111111 |
| M 42 |
| 600 mm x 500 mm |
| 200 mm |
| ± 45° |
| 528 mm |
| 200 mm |
| 370 mm |
| 1123 mm |
| 520 mm |
| |

HEADSTOCK

| Speed range | 50 - 316, 316 - 2000 1/min |
|---------------|-------------------------------|
| Spindle mount | 5 MT |

FEED

| Quill feeds | stufenlos mm/R |
|-------------|----------------|
| | |

DRIVE CAPACITY

| Motor rating main drive | 4 kW |
|--|---------|
| Motor rating for vertical table travel | 0.37 kW |
| Motor rating coolant pump | 0.16 kW |
| | |

MEASURES AND WEIGHTS

| Overall dimensions (length x width x height) | 1.04 m x 0.6 m x 2.27 m |
|--|-------------------------|
| Weight | 950 kg |

SKU: 101680

The drilling machines of the SSB F 60 Super VT series are the servo-conventional solution for every workshop. This machine offers an electronically controlled servo quill feed with a large touchscreen operating display, which also supports the user in selecting the correct machining parameters. Feed and speed are infinitely variable. The entire design of the machine is very solid and the drilling performance is superior. This drilling machine is ideal for single and small series production, especially in the maintenance of large systems and in steel construction and workshops.

- High drilling and thread cutting capacity
- Servo motor for quill feed
- Touchscreen control panel with additional features
- Infinitely variable speed
- Motorized table height adjustments
- Swiveling and rotating setup table
- 3-year Warranty on the Touchscreen



Very heavy construction with thick-walled column



Touchscreen control panel with extended functions



Large drill press table with circumferential coolant groove and ± 45° swivel range



Electronically controlled servo quill feed with thread cutting function

PRODUCT DETAILS

Ideal for drilling, countersinking, reaming and tapping

- Heavy construction with thick-walled column
- Base, column, table and gear head are made of premium high-quality cast iron
- Large drill press table with circumferential coolant groove and $\pm 45^{\circ}$ swivel range
- Table height adjustment via a powerful motorized drive
- Auxiliary gears of main spindle drive run in an oil-bath
- Easy handling of the machine ensures effortless operation in a production environment
- Thread-cutting feature is standard

STANDARD EQUIPMENT

Touchscreen controller
Automatic thread cutting cycles
Automatic drilling feed
Motorised table height adjustment
Accessory set for drilling
Coolant system
Protective shield
LED work lamp
Operator instructions



KNUTH on YouTubeInformation to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

Are you interested in a machine for which you cannot find a current video? Please feel free to contact us!