



SKU : 102641

A vertical band saw is an asset to any workshop that processes steel. Sawing, notching and separating external and internal contours - the models in the VB A series are designed for all-round use and are characterized by their rigid construction, stable work table and variable belt guides

- Swiveling table
- Infinitely variable belt speed
- Adjustable saw blade guide with carbide jaws
- Saw blade welder with shearing and grinding unit



TECHNICAL SPECS

WORKING AREA

Table dimensions	24 in x 22 in
Table with angle adjustment (l/r)	15/45 deg

CUTTING CAPACITIES

Cutting capacity height x throat	11 in x 16 in
Cutting speed	840.39 fpm

DRIVE CAPACITY

Motor rating main drive	2 Hp
Motor rating grinding	0.1 Hp
Blade welder capacity	2.4 kVA

MEASURES AND WEIGHTS

Blade width	0.12 in - 0.59 in
Blade length	133.46 in - 136.5 in
Overall dimensions (length x width x height)	42 in x 37 in x 72 in
Weight	693 lbs



VB 300A



VB 300A



VB 300A

PRODUCT DETAILS

- The machine frame features a torsionally rigid steel construction for a robust and sturdy design
- Functional and practical design, plus easy handling are common features of this entire series
- The support table swivels to the right and left for angled cuts
- The saw blade speed is controlled electronically and shown on a large digital display
- The saw blade guides feature carbide jaws that can be adjusted exactly to different saw blade widths
- Drive gear and idler feature replaceable plastic covers
- Blade tensioning can be micro-adjusted via an accessible hand-wheel
- The standard micro-cooling spray increases saw blade life, saves machining time and reduces cost

STANDARD EQUIPMENT

Saw blade welder assembly
Saw blade shears
Work lamp
Saw-band
Coolant system
Adjustable table stop
Operator instructions