



SKU : 102641

A vertical band saw is an asset to any workshop that processes steel. Sawing, notching and separating external and internal contours - the models in the VB A series are designed for all-round use and are characterized by their rigid construction, stable work table and variable belt guides

- Swiveling table
- Infinitely variable belt speed
- Adjustable saw blade guide with carbide jaws
- Saw blade welder with shearing and grinding unit

TECHNICAL SPECS

WORKING AREA

Table dimensions	600 mm x 550 mm
Table with angle adjustment (l/r)	15/45 deg

CUTTING CAPACITIES

Cutting capacity height x throat	285 mm x 400 mm
Cutting speed	257 m/min

DRIVE CAPACITY

Motor rating main drive	1.5 kW
Motor rating grinding	0.09 kW
Blade welder capacity	2.4 kVA

MEASURES AND WEIGHTS

Blade width	3 mm - 15 mm
Blade length	3390 mm - 3467 mm
Overall dimensions (length x width x height)	1.05 m x 0.92 m x 1.82 m
Weight	315 kg



VB 300A



VB 300A



VB 300A

PRODUCT DETAILS

- The machine frame features a torsionally rigid steel construction for a robust and sturdy design
- Functional and practical design, plus easy handling are common features of this entire series
- The support table swivels to the right and left for angled cuts
- The saw blade speed is controlled electronically and shown on a large digital display
- The saw blade guides feature carbide jaws that can be adjusted exactly to different saw blade widths
- Drive gear and idler feature replaceable plastic covers
- Blade tensioning can be micro-adjusted via an accessible hand-wheel
- The standard micro-cooling spray increases saw blade life, saves machining time and reduces cost

STANDARD EQUIPMENT

Saw blade welder assembly
Blade cutting unit
Work lamp
Saw-band
Coolant system
Adjustable material stop for table
Operator instructions