



### SKU : 102642

A vertical band saw is an asset to any workshop that processes steel. Sawing, notching and separating external and internal contours - the models in the VB A series are designed for all-round use and are characterized by their rigid construction, stable work table and variable belt guides

- Swiveling table
- Infinitely variable belt speed
- Adjustable saw blade guide with carbide jaws
- Saw blade welder with shearing and grinding unit

## TECHNICAL SPECS

### WORKING AREA

Table dimensions	700 mm x 660 mm
Table with angle adjustment (l/r)	15/30 deg

### CUTTING CAPACITIES

Cutting capacity height x throat	310 mm x 500 mm
Cutting speed	15 m/min - 328 m/min

### DRIVE CAPACITY

Motor rating main drive	1.5 kW
Motor rating grinding	0.09 kW
Blade welder capacity	2.4 kVA

### MEASURES AND WEIGHTS

Blade width	3 mm - 16 mm
Blade length	3980 mm - 4050 mm
Overall dimensions (length x width x height)	1.25 m x 1.04 m x 1.98 m
Weight	410 kg



VB 300A



VB 300A



VB 300A

## PRODUCT DETAILS

- The machine frame features a torsionally rigid steel construction for a robust and sturdy design
- Functional and practical design, plus easy handling are common features of this entire series
- The support table swivels to the right and left for angled cuts
- The saw blade speed is controlled electronically and shown on a large digital display
- The saw blade guides feature carbide jaws that can be adjusted exactly to different saw blade widths
- Drive gear and idler feature replaceable plastic covers
- Blade tensioning can be micro-adjusted via an accessible hand-wheel
- The standard minimum quantity cooling device increases the service life of the saw blade, saves machining time and reduces costs

## STANDARD EQUIPMENT

Saw blade welder assembly  
 Blade cutting unit  
 Work lamp  
 Saw-band  
 Coolant system  
 Adjustable material stop for table  
 Operator instructions