



Vertical Bandsaws VB 585 A



SKU : 102643

A vertical band saw is an asset to any workshop that processes steel. Sawing, notching and separating external and internal contours - the models in the VB A series are designed for all-round use and are characterized by their rigid construction, stable work table and variable belt guides

- Swiveling table
- Infinitely variable belt speed
- Adjustable saw blade guide with carbide jaws
- Saw blade welder with shearing and grinding unit

TECHNICAL SPECS

WORKING AREA

| | |
|-----------------------------------|---------------|
| Table dimensions | 28 in x 26 in |
| Table with angle adjustment (l/r) | 15/30 deg |

CUTTING CAPACITIES

| | |
|----------------------------------|---------------|
| Cutting capacity height x throat | 13 in x 23 in |
| Cutting speed | 1111.8 fpm |

DRIVE CAPACITY

| | |
|-------------------------|---------|
| Motor rating main drive | 2 Hp |
| Motor rating grinding | 0.1 Hp |
| Blade welder capacity | 2.4 kVA |

MEASURES AND WEIGHTS

| | |
|--|-----------------------|
| Blade width | 0.24 in - 0.75 in |
| Blade length | 174.41 in - 177.95 in |
| Overall dimensions (length x width x height) | 53 in x 42 in x 84 in |
| Weight | 1221 lbs |



VB 300A



VB 300A



VB 300A

PRODUCT DETAILS

- The machine frame features a torsionally rigid steel construction for a robust and sturdy design
- Functional and practical design, plus easy handling are common features of this entire series
- The support table swivels to the right and left for angled cuts
- The saw blade speed is controlled electronically and shown on a large digital display
- The saw blade guides feature carbide jaws that can be adjusted exactly to different saw blade widths
- Drive gear and idler feature replaceable plastic covers
- Blade tensioning can be micro-adjusted via an accessible hand-wheel
- The standard micro-cooling spray increases saw blade life, saves machining time and reduces cost

STANDARD EQUIPMENT

Saw blade welder assembly
Saw blade shears
Work lamp
Saw-band
Coolant system
Adjustable table stop
Operator instructions