Belt/Disk Sanders

BTM 250

SKU : 112700

The heavy, compact combination belt grinder has a large grinding surface with an endless grinding belt that can be used horizontally and vertically. A dust collection system can be connected via a nozzle. The grinding disc with an angle-adjustable table made of sturdy cast iron in front of it, is particularly suitable for sanding outer radii or angles on narrow workpiece ends. The grinding speed can also be varied for finer machining using the radius of the disc.

- Large grinding area for deburring and removal
- Heavy construction with rigid base
- Disc grinding area with solid angle table
- Vertical and horizontal surface grinding
- Ready for vacuum exhaust connection

TECHNICAL SPECS

WORKING AREA

Belt speed	328 in/s
Speed	1600 rpm
Table area, belt-grinding-	6 in x 11 in
Table area, disc-grinding	7 in x 13 in
Angular adj. of table	45°

DRIVE CAPACITY

Motor rating main drive	1.5 Hp

MEASURES AND WEIGHTS

Sanding pad diameter	10 in
Blade dimensions	5.91 in x 48.03 in
Overall dimensions (length x width x height)	24 in x 26 in x 62 in
Weight	172 lbs

© 2024 KNUTH Werkzeugmaschinen GmbH. All rights reserved
Published on: 08/22/2024

Vertical grinding surface with support table

PRODUCT DETAILS

- Support table for disk and belt grinding
- Easy belt change with quick-lock mechanism
- Including steel base
- Belt sander can be used horizontally and vertically
- Dust suction connector at disk and belt sander unit
- Balanced sander disk for vibration-free operation

STANDARD EQUIPMENT

Base
Dust suction connector
Stops
Sanding belt
Grinding wheel

© 2024 KNUTH Werkzeugmaschinen GmbH. All rights reserved
Published on: 08/22/2024