



Guillotine Shears KMT S 1353

SKU : 133610

The KMT S series has stable construction and is of high quality. The modern guillotine shears have a powerful, motorised drive that enables high cutting performance. The construction with guided cutting blades and a small cutting angle enables cuts with little twist in the workpiece. The backgauge can be precisely positioned using the handwheel accessible from the front.

- Solid steel weldment
- Blades with multiple cutting surfaces
- Back gauge can be positioned from the front of the machine
- Work area is secured by light curtain



TECHNICAL SPECS

WORKING AREA

Working length	53 in
Cutting angle	2.32 deg
Work table height	33 in
Work table depth	15 in
Number of support arms	2 positions
Support arms	37 in
Strokes per minute	34 H/min

BACK GAUGE

Rear stop	30 in
-----------	-------

CUTTING CAPACITIES


Plate thickness (max.) - 450 N/mm ²	0.004 in - 0.118 in
Plate thickness(max.) - 700 N/mm ²	0.059 in

DRIVE CAPACITY

Motor rating main drive	4 Hp
-------------------------	------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	76 in x 85 in x 52 in
Weight	2750 lbs



PRODUCT DETAILS

Machine Frame and Drive System

- The machine frame is made of a very rigid, solid steel weldment
- The upper knives are reversible for use of both sides, and the lower knives feature 4 cutting edges
- A rigid, continuous hold-down fixes the sheet metal plate right in front of the cut line

Material Support

- The rigid side angle stop simplifies alignment of the plate to the cut line
- Rugged support arms ensure a strong hold of large plates
- Material support rollers are recessed in the table for easy workpiece handling

Ergonomic Design

- The mobile foot switch gives the operator added flexibility and both hands are free for handling the workpiece
- For a better view of the cut line, the hand safety guard can be flipped up or down
- The bright LED illumination of the cut line creates a clearly visible shadow on the marked line

Rear stop:

- The back gauge can be positioned precisely via a hand-wheel
- The easy accessible work area at the back gauge is secured by light curtain
- The machine can be equipped with an optional NC-controlled back gauge for a length up to 39", or a sheet hold-up device

STANDARD EQUIPMENT

- Foot pedal with emergency stop switch
- Cut-line lighting
- Squaring arm
- Support arms with T-slots and tilting stop
- Manual 29.5 in. backgauge
- Ball bearing front table
- Light curtain
- Top blade with 2 sides
- Finger guard
- Operator instructions

OPTIONAL EQUIPMENT

- Motorized back gauge 30" (BRL 401.2 NC), SKU : 253664
- Motorized back gauge 39" (BRL 401.2 NC), SKU : 253665
- Adjustable angle stop 0- 180° for KMT S, SKU : 253666
- Pneumatic sheet hold-up device for KMT S, SKU : 253667
- Extra blade kit for KMT S 1353 - 133610, SKU : 253803