

Horizontal Mitre Cutting Bandsaws **SBS 255**



SKU: 152786

The SBS Series Universal Workshop Band Saws are compact machines with swiveling saw frames. The saw frame swivels to right and to the left. The user can guide the saw frame by hand or via the hydraulic valve controlled hydraulic feed. Their design and equipment make these machines very suitable for efficient machining of small batches.

- One-piece cast-iron saw frame
 Rigid vise with long stroke
 High cutting capacity
 Compact design
 Quick-action angle adjustment left

TECHNICAL SPECS

CUTTING CAPACITIES

| Cutting capacity 0° (round) | 255 mm |
|---|-----------------|
| Cutting capacity 0° (square) | 230 mm |
| Cutting capacity 0° (flat) (length x width) | 315 mm x 230 mm |
| Cutting capacity (-) 45° (square) | 160 mm |
| Cutting capacity 45° (flat) L (length x width) | 160 mm x 160 mm |
| Cutting capacity 45° (round) L | 160 mm |
| Cutting capacity 45° (square) R | 195 mm |
| Cutting capacity 45° (round) R | 195 mm |
| Cutting capacity 45° (flat) R (length x width) | 195 mm x 230 mm |
| Cutting capacity 60° R (round) | 115 mm |
| Cutting capacity 60° R (square) | 115 mm |
| Cutting capacity 60° R (flat) (length x width) | 115 mm x 160 mm |
| Cutting speed | 35 / 70 m/min |
| | |

DRIVE CAPACITY

Motor rating main drive 1.5 kW

MEASURES AND WEIGHTS

| Saw blade dimensions | 2750 mm x 27 mm x 0.9 mm |
|--|-----------------------------|
| Overall dimensions (length x width x height) | 1.72 m x 0.73 m x 1.13 m |
| Weight | 375 kg |
| | · |





PRODUCT DETAILS

- Rigid vise with lateral slide, long stroke and long guideways in the movable jaw segments
- The one-piece cast-iron saw frame is torsion-proof and swivels 60° to the right, and 45° to the left
- Rigid saw blade guides offer a wide adjustment range for workpieces with small and large cross-sections
- The combination of carbide jaws and adjustable ball bearing guides ensure precision cuts
- A wide bi-metallic saw blade ensures additional stability during heavy machining operations
- Saw frame features manual feed for sensitive workpiece characteristics
- Hardened, polished helical gear with large bronze drive wheel for long service life
- Quiet operation, short machining times and easy handling ensure increased productivity
- Powerful motor for continuous operation
- High-capacity coolant system is included
- Includes base
- 2 saw blade speeds, selectable at the drive motor
- Mechanical quick-action clamping allows for quick release and fixation of workpieces via hand-lever; ideal for small batches
- The SBS 255 features a round setup table, which pivots in synchrony with the saw frame

STANDARD EQUIPMENT

1 saw blade Coolant system Base Pressure gauge for saw blade tensionig Hydraulic cylinder for saw frame Operator instructions



KNUTH on YouTubeInformation to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

Are you interested in a machine for which you cannot find a current video? Please feel free to contact us!