



Column Drilling Machines TSB 35



SKU : 162301

The TSB bench drill series impresses with its compact dimensions and high drilling performance for a wide range of applications. They are suitable for every workshop, from steel construction to repair shops. The machines have a main spindle gearbox for high torque and a particularly wide speed range. A swiveling drill head enables drilling at an angle. The TSB 35 also has an automatic quill feed for large drilling diameters.

- Compact table design
- Swiveling drill head
- Manual transmission for high torque



TECHNICAL SPECS

WORKING AREA

Drilling capacity	35 mm
Tapping capacity, steel	M 22
Foot set up area (length x width)	370 mm
Vertical head travel	515 mm
Spindle nose-to-foot distance	645 mm
Throat depth	320 mm
Column diameter	120 mm

Weight 340 kg

HEADSTOCK

Spindle speed	125 1/min - 3030 1/min
Spindle mount	4 MT
Quill stroke	155 mm

FEED

Quill feeds	(3) 0,1; 0,2; 0,3 mm/R
-------------	------------------------

DRIVE CAPACITY

Motor rating main drive	1.2 kW
-------------------------	--------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	0.81 m x 0.5 m x 1.67 m
--	-------------------------

PRODUCT DETAILS

High Power at a Low Price

- Drilling capacity 35 mm
- Throat 320 mm
- Spindle nose-to-foot distance 645 mm
- Spindle speed (12) 125-3030 rpm
- Spindle mount MT 4
- Rigid cast-iron construction
- Height-adjustable machine head
- 6 or 12 speed levels
- Rectangular table with T-slots and circumferential coolant groove
- Automatic quill feed
- Digital speed (rpm) display
- Coolant system
- Head swivels $\pm 45^\circ$
- Tapping feature



Swiveling drill head and automatic feed with 3 gear steps



TSB 25: compact design with manual transmission



All switches and controls are clearly labeled

STANDARD EQUIPMENT

Base
Protective shield
Thread cutting function
LED work lamp
Coolant system
Drill chuck
Operating tools
Operating manual