



SKU : 162340

The TSB bench drill series impresses with its compact dimensions and high drilling performance for a wide range of applications. They are suitable for every workshop, from steel construction to repair shops. The machines have a main spindle gearbox for high torque and a particularly wide speed range. A swiveling drill head enables drilling at an angle. The TSB 35 also has an automatic quill feed for large drilling diameters.

- Compact table design
- Swiveling drill head
- Manual transmission for high torque

TECHNICAL SPECS

WORKING AREA

Drilling capacity	0.98 in
Tapping capacity, steel	M 16
Foot set up area (length x width)	12 in
Vertical head travel	19 in
Spindle nose-to-foot distance	26 in
Throat depth	9 in
Column diameter	4 in

HEADSTOCK

Spindle speed	125 rpm - 2825 rpm
Spindle mount	3 MT
Quill stroke	4 in

FEED

Quill feeds	- "/rev
-------------	---------

DRIVE CAPACITY

Motor rating main drive	1 Hp
-------------------------	------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	28 in x 17 in x 62 in
Weight	484 lbs



PRODUCT DETAILS

High Power at a Low Price

- Drilling capacity 0.98"
- Throat 9.4"
- Spindle nose-to-foot distance 26"
- Spindle speed (6) 125-2825 rpm
- Spindle mount MT 3
- Rigid cast-iron construction
- Height-adjustable machine head
- 6 speed steps
- Rectangular table with T-slots and circumferential coolant groove

STANDARD EQUIPMENT

Base
Protective shield
LED work lamp
Drill chuck
Operating tools
Operator instructions