



SKU : 162340

The TSB bench drill series impresses with its compact dimensions and high drilling performance for a wide range of applications. They are suitable for every workshop, from steel construction to repair shops. The machines have a main spindle gearbox for high torque and a particularly wide speed range. A swiveling drill head enables drilling at an angle. The TSB 35 also has an automatic quill feed for large drilling diameters.

- Compact table design
- Swiveling drill head
- Manual transmission for high torque



TECHNICAL SPECS

WORKING AREA

Drilling capacity	25 mm
Tapping capacity, steel	M 16
Foot set up area (length x width)	310 mm
Vertical head travel	470 mm
Spindle nose-to-foot distance	650 mm
Throat	240 mm
Column diameter	95 mm

HEADSTOCK

Spindle speed	125 1/min - 2825 1/min
Spindle mount	3 MT
Quill stroke	110 mm

FEED

Quill feeds	- mm/R
-------------	--------

DRIVE CAPACITY

Motor rating main drive	0.75 kW
-------------------------	---------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	0.7 m x 0.41 m x 1.56 m
Weight	220 kg



PRODUCT DETAILS

High Power at a Low Price

- Drilling capacity 25 mm
- Throat 240 mm
- Spindle nose-to-foot distance 650 mm
- Spindle speed (6) 125-2825 rpm
- Spindle mount MT 3
- Rigid cast-iron construction
- Height-adjustable machine head
- 6 speed steps
- Rectangular table with T-slots and circumferential coolant groove

STANDARD EQUIPMENT

Base
Protective shield
LED work lamp
Drill chuck
Operating tools
Operator instructions