



SKU : 162366

The high-speed radial drilling machines of the KSR series are designed according to the machining principle "tool to workpiece" and are often used in maintenance and in tool and steel construction. The design offers unique flexibility and plenty of work space for larger workpieces, so that one side of the workpiece can be completely machined without repositioning. The machine frame offers clamping surfaces for clamping devices and workpieces on three sides. The quill feed can be varied in four stages by gearbox and with a manually mechanically adjustable depth stop.

- Linear guides for smooth, high-precision movement of the arm
- 3 work stations
- Quill feed with gearing
- Digital depth display
- Tapping unit
- Wide range of accessories

TECHNICAL SPECS

WORKING AREA

Drilling capacity	1.57 in
Tapping capacity, steel	M 30
Throat	37 in
Spindle nose-to-table surface distance	30 in
Column stroke	15 in
Quill stroke	8 in
Head swivel range	± 90°
Column diameter	9 in
Table set up area	47 in x 20 in
Number of T-slots	3 positions
T-slots, width	0.7 in

TRAVELS

Upper beam travel	23 in
-------------------	-------

HEADSTOCK

Spindle mount	4 MT
Spindle speed (infinitely variable)	50 rpm - 2000 rpm

FEED

Feeds	0 in/R - 0.02 in/R
-------	--------------------

DRIVE CAPACITY

Motor rating main drive	3 Hp
Motor rating height adjustment	2 Hp
Motor rating coolant pump	0.5 Hp

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	68 in x 48 in x 89 in
Weight	6028 lbs



PRODUCT DETAILS

- Powerful machine for drilling, tapping, countersinking and boring
- Large travel ranges and many different machining stations provide maximum setup and machining possibilities
- Extremely sturdy construction ensures high accuracy and reliability
- Quick and precise tool positioning: hydraulic clamping is released by the push of a button, head easily swivels forward, backward and horizontally
- Motorized up and down movement of drill head
- Height can be adjusted without changing the drilling position
- Provides great flexibility when machining large parts
- Drill head swivels ± 90 degrees
- Automatic feed with depth stop trigger
- Thick-walled column and large dimensions of all components ensure maximum accuracy
- Digital boring depth display
- Infinitely variable spindle speed with digital display and a digital drilling depth indicator provide extra convenience for the operator

STANDARD EQUIPMENT



- Digital speed indicator
- Additional setup areas at the side and rear
- Cube table
- Swiveling horizontal table
- Digital boring depth indicator
- Work lamp
- Coolant system
- Thread cutting function
- Drill chuck with tool-holder bits
- Operating tools
- Operator manual

