

Column Drilling Machines **KB 32 SF**





TECHNICAL SPECS

WORKING AREA

Drilling capacity	32 mm
Tapping capacity (max.)	M 24
Table set up area	330 mm x 330 mm
Spindle nose-to-table surface distance	813 mm
Spindle nose-to-foot distance	1236 mm
Throat	265 mm
Column diameter	100 mm
Quill stroke	150 mm

HEADSTOCK

Speed range	320 1/min - 1820 1/min
Spindle mount	3 MT

DRIVE CAPACITY

Motor rati	ng main	drive	1.5	kW
------------	---------	-------	-----	----

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	1 m x 0.6 m x 2.1 m
Weight	345 kg

SKU:170461

The KB-S series is a reliable bench drill series for workshops and industry. The machines convince with a compact and modern design, high rigidity and excellent workmanship. These models are part of the basic equipment every mechanical workshop needs.

- Compact and powerful
 Digital speed display
 Tapping feature
 Integrated work light
 Delivered with drill chuck and vise

PRODUCT DETAILS

- Modern design, high-quality cast-iron, and excellent workmanship combined with superior rigidity, function and appearance Heavy, precision-ground work table with diagonal T-slots
- •
- Very smooth height adjustment of drill table, even under high loads
- Large base plate with ground setup area and parallel T-slots
 Forward and reverse, plus automatic reversal of direction for thread cutting
 Spindle shank and spindle are hardened and ground
- Robust belt drive and quiet, powerful motor
 Integrated LED work lamp is standard
- S-series models with digital speed indicator

STANDARD EQUIPMENT

Coolant system Drill chuck Tool-holder bits Drill press vise Thread cutting function Operating tools