

Vertical Machining Centers X.mill T 800 FA



SKU: 181444

The X.mill T series is the newest generation of our vertical machining centers, with modern high-performance compact CNC controls. Whether equipped with Siemens or Fanuc controls, this series offers an excellent price-performance ratio. Wide range of accessories for easy adaptation to meet your specific requirements. Using state-of-the-art FEM Analysis Software, we were able to achieve the highest machine frame rigidity in this machine class

- Optimized frame design using FEM analysis
- Extra wide Y-shaped column for increased rigidity
- Ø32 mm C3 preloaded ball screws for high accuracy
- Available with Siemens or Fanuc control
- High customization and automation possibilities

TECHNICAL SPECS

WORKING AREA

Table dimensions	35 in x 22 in
Table load capacity	1760 lbs
Spindle nose-to-table surface distance	4 in - 26 in
Spindle center-to-stand distance	20 in
Number of T-slots	5 positions
T-slot (width x spacing)	0.71 in x 3.15 in

TRAVELS

Travel X-axis	31.5 in
Travel Y-axis	20 in
Travel Z-axis	22 in

HEADSTOCK

Spindle speed	10000 rpm
Spindle mount	SK 40 ISO 7388-1 (DIN 69871)
Spindle torque (max.)	39 ft.lb.

RAPID FEED

Rapid feed X-, Y-, Z- axis	1417 in/min
----------------------------	-------------

FEED

Work feed	393.7 in/min	

TOOL HEAD

Number of tool stations	20 positions
Tool Ø	100 (130) in
Tool weight max.	18 lbs
Tool-change time tool/tool	10 sec

ACCURACIES

Positioning accuracies	± 0,0002" in
Repeatabilities	± 0,00012" in

DRIVE CAPACITY

Motor rating main drive	14.8 Hp
Motor rating X-axis	2.4 Hp
Motor rating Y-axis	2.4 Hp
Motor rating Z-axis	4.02 Hp
Total power consumption	15 kVA - 20 kVA

CONTROL

Control	Fanuc

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	98 in x 87 in x 100 in
Weight	9680 lbs



Solid machine table with 5 slots



Cast iron body with large span



High quality roller guides



Control Fanuc Oi-MF



PRODUCT DETAILS

- The new X.mill series is ideally suited for streamlined and cost effective series production
- The entire series is optionally available with modern compact CNC controls from Siemens or Fanuc and thus offers the right control solution for many companies.

Machine Design

- The X.mill series machine frame was developed using the most advanced FEM analysis software on the market
- The thorough analysis of the entire machine bed construction and wide column base resulted in a design that is optimized for all load conditions
- All axes move on premium, fully enclosed linear guideways and precision ball screws and are driven by dynamic servo-motors

Spindle

- The main spindle is supported by multiple bearings to ensure excellent absorption and dissipation of forces during machining
- The advanced design of our spindles ensure low heat accumulation under load
- Large preloaded bearings ensure radial stability during heavy-duty machining operations
- High-temperature lubricants ensure optimum lubrication at any operating temperature and a long tool life

Tool Changer

- The robust armless 20-station tool changer brings flexibility to everyday production operations
- An optional 30-station tool changer with dual-arm gripper is also available

Handling

- The totally enclosed workspace features a large door and side doors for easy access, safety and cleanliness
- An electronic hand-wheel simplifies machine set-up
- Electrical equipment is divided into separate control cabinets for high and low voltage systems, which results in a significant reduction of heat accumulation and noise
- The automatic central lubrication system ensures proper lubrication of all lube points

CONTROLS & SOFTWARE

Fanuc Oi-MF control

Fanuc Oi MF control

- Easy programming and operation, short learning curve
- User-friendly graphics display for visual verification of parts programs
- Use of existing programs without reprogramming requirements
- High-speed machining and standard nano-interpolation
- Fixed cycles and custom macro B for simplified parts programming
- State-of-the-Art functionality, like jerk limitation, nano smoothing, and Al Contour Control II - compatibile with previous version series 0 and series 0i models A, B, C and
- Series 0i Model F are the successor models of the Series 0 and Series 0i, which are the most popular CNC controls worldwide with over 700,000 installations.
- With up to 4 simultaneously controlled axes, the CNC Series 0i provides the best controls for highly demanding machine tools.

STANDARD EQUIPMENT

Fanuc Oi-MF control Shield-type 20-station tool changer Screw-type chip conveyor with bucket Rigid tapping Autom. Power-Off Manual coolant spray gun Coolant system Spindle air system Heat exchanger for electric control cabinet Fully enclosed work space (without top cover) Electronic hand-wheel **USB** port Automatic central lubrication Work lamp 3-color signal lamp Operating tools Alignment bolts and alignment plates Prepared for Renishaw TS 27 R

OPTIONAL EQUIPMENT

- Top cover for X.Mill/Vector 650-1000, SKU: 252819
- Upgrade Fanuc Oi-MF (package 5 to package 1), SKU: 252888
- Manual guide 0i, SKU: 252889
- Connection for 4th axis (wiring only and axis chart), SKU: 253019
- Coolant flow through spindle, 30 bar, with filter system, SKU: 253369
- Oil skimmer, SKU: 253383
- Chip flush-out system, SKU: 253384
- Dual-arm gripper with 24 tool stations, BT40, SKU : 253436 Spindle oil cooler, SKU : 253440
- Spindle speed upgrade 10,000 to 12,000 rpm (belt type), SKU: 253609
- Spindle speed upgrade to 12,000 rpm direct drive without CTS, SKU: 253610
- Upgrade ATC from 24 to 30 tools (BT40), SKU: 253611
- Upgrade: from worm-gear chip conveyor to chain-drive chip conveyor, SKU: 253612
- Manual tailstock ST-125T for rotary table, SKU: 253617 Manual tailstock ST-170T for rotary table, SKU: 253618
- Manual tailstock ST-255T for rotary table, SKU: 253620
 Manual chuck, 5", for rotary table, SKU: 253621

- Manual chuck, 6", for rotary table, SKU: 253622
 Manual chuck, 9", for rotary table, SKU: 253624
 Preparation for CTS Setup, SKU: 253626
- Coolant flow through spindle, 290 psi, with filter system, SKU: 253627
- Manual guide i (requires Fanuc Package 1), SKU: 253631
- 4.92" diam. 4th axis (4th axis, servo motor, driver, air brakes)(Fa), SKU: 253639
- 6.69" diam. 4th axis (4th axis, servo motor, driver, air brakes)(Fa), SKU: 253640
- 8.27" diam. 4th axis (4th axis, servo motor, driver, air brakes)(Fa), SKU: 253641
- 9.84" diam. 4th axis (4th axis, servo motor, driver, air brakes)(Fa), SKU: 253642
- Air through spindle, SKU: 253782
- Spindle upgrade from ST40 to BBT40 for X.Mill/Vector 650-1000, SKU: 253951
 - (Wasbek) Renishaw OMP40-2T Workpiece Scanning Probe (ST 40), SKU: 253288

- (Wasbek) Renishaw SET OMP40-2T Scanning Probe + OTS Toolsetter (ST 40), SKU: 254026
- (Wasbek) Renishaw OTS Toolsetter, SKU: 254285