



Vertical Machining Centers LabCenter 260 CNC



SKU : 181615

The LabCenter is ideal for CNC training, but also for the production of small workpieces. The compact and mobile CNC machining center represents the full range of functions of a large production machine. The main spindle rotates continuously variable up to 5000 revolutions and the Siemens 808 control offers an ideal introduction to CNC applications with its simple, intuitive operator guidance. With the ISO 20 spindle taper, automatic tool clamping and a 4-way pick-up tool changer, the LabCenter enables practice-oriented training.

- SIEMENS 808 Advance is the ideal introductory machine
- Preloaded ball screws on all axes
- Spindle speeds up to 5000 rpm
- 4-station tool changer
- Mobile machine base with storage space

TECHNICAL SPECS

WORKING AREA

Table dimensions	16 in x 6 in
Table load capacity	44 lbs
Number of T-slots	3 positions
T-slots, width	0.5 in
T-slots, spacing	1.6 in
Spindle nose-to-table surface distance	2 in - 9 in
Throat	8 in

TRAVELS

Travel X-axis	6.3 in
Travel Y-axis	6 in
Travel Z-axis	7 in

HEADSTOCK

Spindle speed	80 rpm - 5000 rpm
Spindle mount	SK 20 ISO 7388-1 (DIN 69871)

RAPID FEED

Rapid feed X-axis	78.74 in/min
Rapid feed Y-axis	78.74 in/min
Rapid feed Z-axis	78.74 in/min

FEED

Work feed	20 in/min
Work feed X-axis	19.685 in/min
Work feed Y-axis	19.685 in/min
Work feed Z-axis	19.685 in/min
Max. torque feed motor X-axis	1.62 ft.lb.
Max. torque feed motor Y-axis	1.62 ft.lb.
Max. torque feed motor Z-axis	1.62 ft.lb.

TOOL HEAD

Number of tool stations	4 positions
Tool size Ø x L (max.)	0.39 in x 4.33 in
Tool weight max.	1 lbs
Tool-change time tool/tool	10 sec

ACCURACIES



Positioning accuracy X-axis	± 0,000590 in
Positioning accuracy Y-axis	± 0,000590 in
Positioning accuracy Z-axis	± 0,000590 in
Repeatability X-axis	± 0,0004 in
Repeatability Y-axis	± 0,000393 in
Repeatability Z-axis	± 0,0004 in

DRIVE CAPACITY

Motor rating main drive	1.3 Hp
-------------------------	--------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	56 in x 36 in x 71 in
Weight	990 lbs



Tool holder with 4 positions



PRODUCT DETAILS

Highlights

- Compact, mobile and professional for laboratories and training
- Electronic hand-wheel for efficient and professional set-up
- Mobile base with storage room for tools and materials

Machine Design

- Precisely machined frame made of high-quality cast iron
- Dovetail guides and preloaded ball screws with servo drives on all axes

Spindle

- Max. spindle speeds up to 5000 rpm
- Spindle mount ISO 20

Tool Changer

- 4-station tool changer ensures flexibility and optimum productivity

CONTROLS & SOFTWARE

Siemens 808D Advance control

- SINUMERIK 808D ADVANCE -- the perfect solution for modern standard machines
- CNC and drive communicate via a high-speed bus to ensure efficient positioning control plus high precision and optimum cutting performance
- This is topped by a guaranteed superior price/performance ratio
- In combination with a new generation of spindle and axis drives, the SINUMERIK 808D ADVANCE with 8.4" LCD provides an innovative ready-to-use digital CNC solution for modern standard machines

Advantages - Digital solution provides higher precision:

- Increased overload capacity supports a faster acceleration and deceleration of machine tools
- Constant cutting speeds result in an increased surface quality of the workpiece

Increased ruggedness:

- During heavy machining operations, an automatic spindle torque adjustment will help protect machining tools and spindle systems.
- The SINAMICS features a wide voltage range to prevent machine shut-downs during poor voltage supply conditions. This will significantly reduce machine down-times.

Increased operator comfort:

- A fast Ethernet connection facilitates easy start-up and diagnostics of machine tools and simplifies NC program use

STANDARD EQUIPMENT

- Siemens 808D Advance control
- Electronic hand-wheel
- 4-station tool changer
- Mobile base
- Central lubrication
- Work lamp
- Operating tools
- Operating manual and programming instructions