



### SKU : 301215

The multi-purpose milling machine series MF1 impresses with its design and is indispensable in many repair workshops as well as training and production departments. The X-axis is steplessly adjustable with a feed device and the swiveling vertical milling head with a wide steplessly adjustable speed range processes steel up to non-ferrous metals. The standard accessories include an automatic quill feed and pneumatic tool clamping as well as a mounted position indicator.

- Swiveling, tiltable cutter head with quill feed
- Pneumatic tool tightening system
- Infinitely variable spindle speed
- Feed on X-axis with rapid feed
- Extensive standard equipment

## TECHNICAL SPECS

### WORKING AREA

Table set up area	1245 mm x 230 mm
Number of T-slots	3 positions
T-slot (width x spacing)	16 mm x 63.5 mm

### TRAVELS

Travel X-axis	760 mm
Travel Y-axis	290 mm
Travel Z-axis	370 mm

### VERTICAL MILLING HEAD

Spindle speeds	60 1/min - 4200 1/min
Quill stroke	127 mm
Spindle mount	SK 30 DIN 2080
Throat	171 mm - 476 mm

### FEED

Feed speed X-axis	19 mm/min - 890 mm/min
Quill feeds	(3) 0,04;0,08;0,13 mm/R
Console travel (Z-axis)	370 mm

### DRIVE CAPACITY

Motor rating main drive	2.25 kW
-------------------------	---------

### MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	2.05 m x 1.63 m x 2.07 m
Weight	950 kg



## PRODUCT DETAILS

- The most widely used milling machine type in the world - with standard pneumatic tool clamping
- Infinitely variable spindle speed via hand wheel adjustment
- Larger table with larger travel on X
- TV 1000 automatic table advance on X-axis is included, retrofitting of Y-axis available
- Head swivels on 3 axes: swivel r + l  $\pm 90^\circ$ ; tilt forward + reverse  $\pm 45^\circ$ ; rotation on the column  $\pm 45^\circ$
- Dovetail guides, hardened, adjustable
- 3 automatic drill feeds
- Manual coarse feed for quill, with change-over for manual fine feed
- Quill with automatic micrometer depth stop
- Reversing switch for forward reverse rotation
- Central lubrication for spindle, nut and guides
- Manual spindle brakes
- Pneumatic tool clamping
- 3-axis position indicator, coolant system, and LED work lamp (included in standard equipment)

### 3-axis position indicator

- More accuracy
- Lower error rate
- Increased productivity
- Resulting in valuable time savings
- For increased productivity
- Easy to read display
- Operator-specific features
- Convenient keyboard layout
- Resolution: 0.01/ 0.005 mm
- Default coordinates
- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Calculator function
- Storage for 10 tools
- Radius / diameter toggle
- Mm/inch conversion
- Easy expansion and maintenance-free operation

## STANDARD EQUIPMENT

3-axis position indicator X.Pos 3.2  
 Automatic table feed in X direction (TV 1000)  
 Pneumatic tool clamping  
 Coolant system  
 Central lubrication  
 Vertical guideway cover  
 LED work lamp  
 Operating tools  
 Operator manual