



### SKU : 301217

The versatile multi-purpose milling machine combines all the advantages of the world's best-selling milling machine with additional stability. The top model of the MF series has an SK 40 tool holder and a 30 percent higher unladen weight. The X and Y axis are equipped with infinitely variable feed devices. The swiveling vertical milling head offers a wide speed range for machining steel and non-ferrous metals. The equipment also includes a four-stage, automatic quill feed, pneumatic tool clamping and a large clamping table for workpieces and clamping devices.

- Swiveling cutter head with quill feed
- Pneumatic tool tightening system
- Infinitely variable spindle speed
- Feed on X-axis with rapid feed
- Heavy construction with wide guideways

## TECHNICAL SPECS

### WORKING AREA

Table set up area	1370 mm x 250 mm
Table load capacity (max.)	350 kg

### TRAVELS

Travel X-axis	800 mm
Travel Y-axis	390 mm
Travel Z-axis	380 mm

### VERTICAL MILLING HEAD

Spindle speed (vertical)	70 1/min - 3600 1/min
Spindle mount	SK 40 DIN 2080
Quill stroke	127 mm

### FEED

Quill feeds	(3) 0,04; 0,08; 0,15 mm/R
-------------	---------------------------

### DRIVE CAPACITY

Motor rating main drive	3.75 kW
-------------------------	---------

### MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	2.54 m x 2.16 m x 2.24 m
Weight	1590 kg



*Variable throat widths and machining angles*



*Wide, rigid box ways on Z and Y-axes*

## PRODUCT DETAILS

- More rigid and more powerful with 3.75 kW motor
- ISO 40 spindle
- 3 automatic drill feeds
- Manual coarse feed for quill, with change-over for manual fine feed
- Quill with micrometer depth stop
- Reversing switch for forward reverse rotation
- Spindle brakes
- Infinitely variable speeds
- Head swivels  $\pm 90^\circ$  to the right and to the left
- TV 1000 table feed in X and Y, infinitely variable with rapid feed
- Coolant system
- Chip tray
- Central lubrication
- Pneumatic tool clamping

### 3-axis position indicator

- More accuracy
- Lower error rate
- Increased productivity
- Resulting in valuable time savings
- For increased productivity
- Easy to read display
- Operator-specific features
- Convenient keyboard layout
- Resolution: 0.01/ 0.005 mm
- Default coordinates
- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Calculator function
- Storage for 10 tools
- Radius / diameter toggle
- Mm/inch conversion
- Easy expansion and maintenance-free operation

## STANDARD EQUIPMENT

3-axis position indicator X.Pos 3.2  
 Table feed TV 1000 on X- and Y-axis  
 Pneumatic tool clamping  
 Chip tray  
 Coolant system  
 Central lubrication  
 Horizontal guideway cover  
 Operating tools  
 Operator manual