

Conventional Milling and Boring Machines

BO 130



SKU : 399022

The BO series of conventional boring and milling machines with a fixed column is designed for horizontal multi-sided drilling and milling of workpiece weights of up to 10 tons. The movable table can rotate 360°. The drill head moves on the column and the spindle has a long stroke on the W-axis. Efficient machining and short non-productive times result from high drive power and automatic feeds on all axes with rapid traverses. In addition, these conventional boring mills have a facing slide with a long stroke.

- Large work area with W-axis and facing slide
- Thread cutting unit
- 4 x 90° rotatable set-up table
- Telescoping stainless steel covers on all guides

TECHNICAL SPECS

WORKING AREA

Drilling capacity	60 mm
Table set up area	1600 mm x 1800 mm
Table load capacity	10000 kg
Table rotation range	4 x 90°
Spindle axis-to-table surface distance	0 mm - 1800 mm
Rotation speed of rotary table	1.2 1/min

TRAVELS

Travel X	2000 mm
Travel Y	1800 mm
Travel Z	1500 mm
Travel W	900 mm
Facing slide travel	250 mm

HEADSTOCK

Speed range	4 1/min - 800 1/min
Spindle diameter	130 mm
Spindle torque (max.)	3136 Nm
Spindle mount	SK 50
Facing slide speed	2.5 1/min - 125 1/min
Feed force, axial (max.)	31.36 kN
Facing slide torque (max.)	4900 Nm

RAPID FEED

Rapid feed X-axis	2500 mm/min
Rapid feed Y-axis	2500 mm/min
Rapid feed W-axis	2500 mm/min

FEED

Feed X-axis	0.01 mm/R - 6 mm/R
Feed Y-axis	0.01 mm/R - 6 mm/R
Feed Z-axis	0.01 mm/R - 6 mm/R
Feed W-axis	0.01 mm/R - 6 mm/R
Facing slide feed	0.08 mm/min - 12 mm/min

ACCURACIES


Read-out accuracy (optic)	0.005 mm
Counter-bore accuracy	H7 Ra-1,6 µm

DRIVE CAPACITY

Motor rating main drive	15 kW
Motor rating servo drive	5.5 kW
Motor rating hydraulic pump	0.37 kW

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	7.03 m x 4.66 m x 3.8 m
Weight	29300 kg



PRODUCT DETAILS

- Rigid, hardened and precision-ground square guides ensure many years of accurate operation
- Mechanical functions that cannot be run simultaneously are provided with interlocks
- Headstock and feed gears are equipped with an overload clutch
- Lever-operated shift gears for positioning of the wheels in the desired position
- Faceplate and drill spindle with different task-specific speed ranges according to the various functions
- Table rotates 4 x 90°
- Telescoping steel cover protects the guides from chips and dirt
- BO 110 incl. tailstock (optional on BO 130)

3-axis position indicator

- More accuracy
- Lower error rate
- Increased productivity
- Resulting in valuable time savings
- For increased productivity
- Easy to read display
- Operator-specific features
- Convenient keyboard layout
- Resolution: 0.01/ 0.005 mm
- Default coordinates
- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Calculator function
- Storage for 10 tools
- Radius / diameter toggle
- Mm/inch conversion
- Easy expansion and maintenance-free operation

STANDARD EQUIPMENT

3-axis position indicator X.Pos 3.2
 Wedge strip
 Central lubrication
 Work lamp
 Foundation bolts
 Operating tools
 Operator instructions