

SKU : 822572

USED



TECHNICAL SPECS

WORKING AREA

Center height	280 mm
Workpiece length (max.)	1428 mm
Turning-Ø over bed	560 mm
Turning-Ø over support	355 mm
Turning diameter over gap bridge	785 mm
Gap bridge length	170 mm
Bed width	350 mm

DETAILS

Equipment	m. Posi u. stufenl. Drehzahlverst.
-----------	------------------------------------

TRAVELS

Travel X-axis	316 mm
Travel Z1-axis	130 mm
Swing range of top slide	± 52°

HEADSTOCK

Spindle speeds	L 25-200 / H 200-1600 1/min
Spindle bore	80 mm
Spindle mount	Camlock D1-8
Spindle taper	7 MT

FEED

Feed X-axis	0.02 mm/R - 0.573 mm/R
Feed Z-axis	0.059 mm/R - 1.646 mm/R

THREADING

Threading, metric	0.2 mm - 14 mm
Threading, diametric	(50) 4-112 DP
Threading, module	0.1 mm - 7 mm
Threading, whitworth	(60) 2-112 TPI

TAILSTOCK

Tailstock quill diameter	75 mm
Tailstock taper	5 MT
Tailstock quill stroke	180 mm
Tailstock traverse adjustment	± 12 mm

DRIVE CAPACITY

Motor rating main drive	7.5 kW
-------------------------	--------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	2.84 m x 1.15 m x 1.46 m
Weight	2370 kg

PRODUCT DETAILS

- The Turnado V Series Universal Lathes are widely tested and proven and our definite bestsellers with a low price and lasting high value

Machine bed

- A heavily ribbed machine bed, rigid headstock and a massive one-piece thick-walled cast-iron stand form a solid machine base for efficient and precisely machining
- A removable bridge allows machining of short workpieces with very large diameters
- The wide v-block guideways are hardened and ground for lasting precision

Headstock/ feed gear

- The powerful motor features a modern variable frequency drive, and the two-step main spindle gear ensures high torque across the entire infinitely variable speed range
- The Turnado 230 V series features an extended maximum speed range and a wider application spectrum
- All gears and shafts are hardened and ground and run in an enclosed oil bath
- The large spindle capacity allows clamping of shafts and tubes with large diameters
- The high quality spindle support features optimum rigidity and preloading for high precision even under high radial and axial loads as well as long lasting performance
- A 3-jaw lathe chuck with hard reversible jaws, a 4-jaw independent chuck, and a face plate with large diameter are included in the machine's standard equipment
- The user-friendly control panel facilitates rapid user familiarization and intuitive operation
- The feed gear offers a large number of thread leads for metric and Withworth tapping

Support

- The support is designed extra-wide and can easily handle high machining forces
- The control lever for the feed switch and apron nut provide automatic safety interlocking and reliably prevent operational errors
- The stop spindle features four adjustable cams to provide automatic linear feed shut-off
- This way, repetitive machining processes with different Z axis positions can be simplified by presetting the desired positions in the necessary sequence
- The micrometer bed stop can be used to set precise travel distance limits
- The slip coupling for the automatic feed is positioned centrally on the apron for easy adjustments
- The thread gauge and support allow reliable determination of the pitch after an interrupted tapping process, and also simplifies machining of multi-lead threads
- The top slide swivels and has large, easy to read scaling
- The large, swiveling safety cover at the support protects the user and keeps the work space clean
- A central lubrication system at the support supplies all guideways with lubrication and simplifies maintenance

Tailstock

- The tailstock quill is equipped with a robust and easy to read scale
- The long quill stroke allows for complex drilling and centering jobs
- The tailstock can be adjusted laterally for machining of conical shafts

Accessories

- The standard brake pedal is not only practical, but also a safety feature
- A large and sturdy splash guard on the rear of the machine ensures a clean machine environment
- A bright LED light is integrated in the support cover for optimum lighting throughout the work space
- The multi-functional quick-action tool changer system with 4 tool changer cartridges is included in the standard equipment of this series
- A steady and a live rest are a must for long workpieces and also included in the standard package
- The Turnado Lathe is equipped with the latest generation of our position indicators. Ensures high work precision, lower error rate, and increased operator safety
- Extended X.Pos Position Indicator functionality with the addition of the "V-constant" function
- During facing, the spindle speed is automatically adapted to the changing workpiece diameters, resulting in a surface quality that is comparable to the surface grade achieved with CNC lathes
- A coolant system and extensive operating tools complete the equipment package

STANDARD EQUIPMENT

3-axis position indicator, X.pos 3.2 VC
Quick tool changer head WC
Quick change tool holder WCD 32150
Adjustable feed stops
3-jaw chuck Ø 315 mm
4-jaw face chuck Ø 350 mm
Face plate Ø 450 mm
Follow and steady rests
Coolant system
Micrometer longitudinal stop
Thread gauge
Reducing sleeve
Dead center
Protective shield for the toolpost
Chuck guard
Foot brake pedal
Fixed splash guard (wall)
Work light
Toolbox with operating tools
Operator instructions